



NEON A.S
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005
TIRANA, ALBANIA
TEL: +355 42 377 773 FAX: +355 42 347 770
E-MAIL: info@neon.al WEB: www.neon.al

**NEON ZN – 701
(TAR LINER)**
Technical File

DESCRIPTION: NEON PRIMER ZN - 701 tar is a water-based primer, which contains bituminous fillers. It is flammable and forms a waterproof layer. It sticks perfectly with all construction materials. There is a simple and efficient use.

AREA OF USE: NEON PRIMER ZN - 701 is used for waterproofing vertical or horizontal surfaces of concrete, the old bituminous regeneration and serves as insulating steam. It can also be used as a primer (primer) on which bitumen membrane is placed.

Color: Black dark brown.

USE: Used in cold condition applied by brush, roller or spray gun. Between the two hands it can be reinforced with fiber retina. Dilute with water up to 30%. Each hand consumes 0.3L / m² - 0.4L / m². For a better result more than two coats are recommended. If the use is as a liner then dilute with water up to 50% and consume 0.3L / m². The second coat should be applied only after the first is completely dry. Wash working tools with water if they are not dried, or White Spirit if they are dried.

RISKINESS: NEON PRIMER ZN - 701 should be used in appropriate container to avoid environmental contamination. It should be kept away from children (S 2), irritates eyes and skin (R36 / 38) .In case of skin contact, clean immediately with plenty of water (S 28). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26). Use gloves and mask during application (S 37/39).

PACKAGING: Packaging is made in plastic buckets containing 3L and 9L.

PRESERVING CONDITIONS: In a hermetically closed packaging, protected by frosting.