



NEON A.S  
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005  
TIRANA, ALBANIA  
TEL: +355 42 377 773 FAX: +355 42 347 770  
E-MAIL: [info@neon.al](mailto:info@neon.al) WEB: [www.neon.al](http://www.neon.al)

---

## NEON ZMALTOLAC NORMAL

### Technical File

---

**DESCRIPTION:** NEON ZMALTOLAC NORMAL is a paint glaze based on alkyd resins. It is a high quality plain glaze and it is shiny. It is destined for painting metal surfaces, wood or walls in internal or external environments, in order to protect and decorate structures. Referring to its ingredients, in optimal environmental conditions the paint dries 4-6 hours after application, creating a membrane with high gloss and mechanical toughness. Its external part resists atmospheric agents and retains its color over time.

**AREA OF USE:** NEON ZMALTOLAC NORMAL is usable in internal and external environments, metal surfaces with paints, wooden surfaces and walls.

**COLOR:** NEON ZMALTOLAC NORMAL paints are a great range of colors, which are listed in the catalog of the Company "NEON".

**USAGE:** NEON ZMALTOLAC NORMAL is prepared by first diluting with diluent NC - 10:00 or NX - 20 000 or White Spirit "NEON" NW - 13:30 quantity 10% ÷ 15%, to obtain a consistency of paint which is relatively easy to work with a paintbrush , roller or spray gun. Do not run on vertical surfaces.

**WARNING:** The application of paint on wet and unclean the surfaces is not allowed. During application use suitable gloves to avoid skin contact with paint. If you are using a gun, make sure to wear a protective mask for the protection of your respiratory organs. If it contacts your eyes, you must rinse them with water and seek medical advice. The use of this paint is not recommended in temperatures less than 5°C. After completing the painting, the equipment should be washed immediately with white spirit.

#### TECHNICAL DATA:

- Color.....neon catalog
- Viscosity (30% water) Deep cup 4.....200 -300sec
- Density.....1.1-1.35 g / ml
- Covering power for full painting.....7-8 m<sup>2</sup>/L
- Dry residue.....55%
- Drying time.....4-6 hours\
- Application temperature .....+ 5°C to + 35°C

**RISKINESS:** NEON ZMALTOLAC NORMAL, Attention! Is flammable. It should be used in the appropriate container to avoid environmental pollution. It should be kept away from children (S 2), irritates eyes and skin (R36 / 38). In case of contact with skin, clean immediately with plenty of water (S 28). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S 26). Use gloves and mask during application (S 37/39).

**PACKAGING:** The packaging is done in cans of 0.75 L and 3.75 L

**PRESERVING CONDITIONS:** Stored in environments with temperatures above 0°C, and in hermetically sealed packaging, for more than a year.