



NEON A.S
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005
TIRANA, ALBANI
TEL: +355 42 377 773 FAX: +355 42 347 770
E-MAIL: info@neon.al WEB: www.neon.a

NEON MARTELAC PROFESSIONAL
(DECORATIVE PAINT FOR MACHINERT AND METAL SURFACES)
Technical File

DESCRIPTION: NEON MARTELAC PROFESSIONAL is a synthetic kind of paint, based on resin alkyd and nitrocellulose, high quality and shiny and dries quickly after application. This paint is intended for painting machinery and other metal structures. Referring to its components, in an optimal environment the paint dries 30 min - 5 hours after application, creating a membrane scaled with high gloss and resistance to satisfactory mechanical. It resists external agents and maintains its color over time. There are many good anti-corrosion properties.

AREA OF USE: NEON MARTELAC PROFESSIONAL is a high quality paint. It is recommended for cars and any other machine, giving you not only a sleek look, but also additional protection.

COLOR: NEON MARTELAC PROFESSIONAL paints are a great range of colors, which are listed in the catalog of the Company "NEON"

USAGE: NEON MARTELAC PROFESSIONAL is prepared by first diluting with diluent NC - 10:00 or NX - 20 000 or White Spirit "NEON" NW - 13:30 quantity 10% ÷ 20%, to obtain a consistency of paint which relatively easy to work with a paintbrush , roller or spray gun. Do not run on vertical surfaces.

WARNING: The application of paint on wet and unclean the surfaces is not allowed. During application use suitable gloves to avoid skin contact with paint. If you are using a gun, make sure to wear a protective mask for the protection of your respiratory organs. If it contacts your eyes, you must rinse them with water and seek medical advice. The use of this paint is not recommended in temperatures less than 5°C. After completing the painting, the equipment should be washed immediately with white spirit.

TECHNICAL DATA:

- Color.....neon catalog
- Viscosity (30% water) Deep cup 4..... 150 -200sec
- Density.....1.1-1.2 g / ml
- Covering power for full painting.....7-8 m²/L
- Dry residue.....33%
- Drying time (to touch with hand).....30 min
- Drying time3-4 hours
- Application temperature+ 5°C to + 35°C

RISKINESS: NEON MARTELAC PROFESSIONAL, Attention! It is flammable. It should be used in the appropriate container to avoid environmental pollution. It should be kept away from children (S 2), irritates eyes and skin (R36 / 38). In case of contact with skin, clean immediately with plenty of water (S 28). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S 26). Use gloves and mask during application (S 37/39).

PACKAGING: The packaging is done in cans of 0.75 L.

PRESERVING CONDITIONS: Stored in environments with temperatures above 0°C, and in hermetically sealed packaging, for more than a year.