



NEON A.S  
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005  
TIRANA, ALBANIA  
TEL: +355 42 377 773 FAX: +355 42 347 770  
E-MAIL: [info@neon.al](mailto:info@neon.al) WEB: [www.neon.al](http://www.neon.al)

---

**NEON ANTIRUST PROFFESIONAL**  
**(ANTICORROSIVE PAINT PROFESSIONAL)**

Technical File

---

**DESCRIPTION:** NEON ANTIRUST PROFFESIONAL suspension antirust is a professional high quality alkyd resin based paint, with coating of metal constructions destined to protect against rust and for decoration. Referring to its constituents, it has the property of inhibiting the process of oxidation (rust) of metal surfaces, environments internal and external.

**AREA OF USE:** NEON ANTIRUST PROFFESIONAL used to paint metal surfaces in internal environments and external corrosion protection of these areas, as well as serving as a space filler that may have metal construction.

**COLOR:** NEON ANTIRUST PROFFESIONAL paints are a great range of colors, which are listed in the catalog of the Company "NEON".

**USAGE:** NEON ANTIRUST PROFFESIONAL is prepared by first diluting with diluent NC - 10:00 or NX - 20 000 or White Spirit "NEON" NW - 13:30 quantity 10% ÷ 20%, to obtain a consistency of paint which relatively easy to work with a paintbrush , roller or spray gun. Do not run on vertical surfaces.

**WARNING:** The application of paint on wet and unclean the surfaces is not allowed. During application use suitable gloves to avoid skin contact with paint. If you are using a gun, make sure to wear a protective mask for the protection of your respiratory organs. If it contacts your eyes, you must rinse them with water and seek medical advice. The use of this paint is not recommended in temperatures less than 5°C. After completing the painting, the equipment should be washed immediately with white spirit.

**TECHNICAL DATA:**

- Color.....neon catalog
- Viscosity (30% water) Deep cup 4..... 180 -250sec
- Density.....0.9-1.2 g / ml
- Covering power for full painting.....7-8m<sup>2</sup>/L
- Dry residue.....60%
- Drying time.....2-3 hours\
- Application temperature .....+ 5°C to + 35°C

**RISKINESS:** NEON ANTIRUST PROFFESIONAL, Attention! It is flammable. It should be used in the appropriate container to avoid environmental pollution. Should be kept away from children (S 2), irritates eyes and skin (R36 / 38). In case of contact with skin, clean immediately with plenty of water (S 28). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S 26). Use gloves and mask during application (S 37/39).

**PACKAGING:** The packaging is done in cans of 0.75 L.

**PRESERVING CONDITIONS:** Stored in environments with temperatures above 0°C, and in hermetically sealed packaging, for more than a year.