



NEON A.S
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005
TIRANA, ALBANIA
TEL: +355 42 377 773 FAX: +355 42 347 770
E-MAIL: info@neon.al WEB: www.neon.al

NEON PRIMOLAC PROFFESIONAL
(PROFESSIONAL LINER FOR METALS)

Technical File

DESCRIPTION: NEON PRIMOLAC PROFFESIONAL is used as a liner before the use of glaze paints. PRIMOLAC is mainly used to protect the metal structure from corrosion. It fills defects or holes that might be on a painted surface. Easily cleaned. Referring to its constituents, it has the property of inhibiting the process of oxidation (rust) of metal surfaces, environments internal and external.

AREA OF USE: NEON PRIMOLAC PROFFESIONAL is used to paint metal surfaces in internal environments and external corrosion protection of these areas, as well as serving as a space filler that may have metal construction.

COLOR: Transparent

USAGE: Mix well before use. It can be painted with roller, brush or gun.

WARNING: The application of the liner in wet surfaces and in conditions of high humidity, IS NOT ALLOWED. It is also not advisable to use under 5°C

TECHNICAL DATA:

- Color.....Transparent
- Viscosity (30% water) Deep cup 4.....15– 60 sec
- Density.....0.94-1.1g / ml
- Covering power for full painting.....10-12 m²/L
- Dry residue.....35%
- Drying time.....2 hours\
- Application temperature+ 5°C to + 35°C
- Resistance to alkalis..... excellent

RISKINESS: NEON PRIMOLAC Attention! It is flammable. It should be used in appropriate the container to avoid environmental pollution. It should be kept away from children (S 2), irritates

eyes and skin (R36 / 38). In case of contact with skin, clean immediately with plenty of water (S 28). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S 26). Use gloves and mask during application (S 37/39).

PACKAGING: The packaging is done in cans of 0.75 L.

PRESERVING CONDITIONS: Stored in environments with temperatures above 0°C, and in hermetically sealed packaging, for more than a year.