



NEON A.S
RR.XHANFISE KEKO, Nd.168 , H.1, CP. 1005
TIRANA, ALBANIA
TEL: +355 42 377 773 FAX: +355 42 347 770
E-MAIL: info@neon.al WEB: ww.neon.al

NEON UNO COLOR PAINT
PIGMENT FOR PAINTING WALLS
Technical File

DESCRIPTION: UNO COLOR PAINT is destined for painting exterior facades and interior surroundings, or for the pigmentation of white paint, according to the NEON catalog. It is composed by PVA VEOVA resins of high quality. It is appropriate for stucco-d, plastered, cemented etc. surfaces. The painted surface, after drying for 15-20 days, can be cleaned with a cleaning solvent, rinsed thoroughly with water and can be dried without causing the paint to be erased.

AREAS OF USAGE: UNO COLOR PAINT can be used in interior and exterior surroundings.

COLOR: Black, brown, yellow, chocolate brown, green, ochre, red, blue, orange.

PREPARATION: The surface which will be painted, should be clear of all powder dusts, fats or previous paint layers, connected weakly to the surfaces (swollen layers). In new surfaces, you have to use a coat of plastic liner PN-301 in advance, which can be diluted with water up to 30%, or plastic liner PN- 101 which is ready for use.

USAGE: The paint is prepared by adding water to the wanted consistency. To achieve a good result, you must apply two coats of UNO COLOR PAINT in advance. During the first coat, the paint dilution with water should be in the ratio of 10%. 2-4 hours later, apply the second coat. The paint can be easily applied with rollers or brushes.

WARNING: The application of the liner in wet surfaces and in conditions of high humidity, IS NOT ALLOWED. It is also not advisable to use it under 5°C. After painting, the tools must be immediately washed with water and soap.

TECHNICAL DATA:

- Color..... According to catalog
- Drying time..... 2-4 hours

RISKINESS: "NEON sh.a" water basis paintings have components which are not classified as dangerous, based on the Directive 1999/45/EC.

PACKAGING: Packaging is made in metallic boxes 0.188L, 0.375L and 0.75L.